

Whether you are a high wire grower in the United Kingdom, Finland, Canada or France, get a better, more energy efficient lighting solution to grow right through the darker periods during the year. Based on input from growers around the world, our new GreenPower LED interlighting system allows you to grow and harvest fresh and flavorful tomatoes or cucumbers year round, no matter where you are or what energy prices you face. Placing light between your plants lets you achieve the maximum value and return from your production and your electricity costs for lighting.

Plug and play system reduces installation costs

The interlighting system comes with an easy plug and play connector and just a few cables and accessories. Connect up to 33* interlighting modules with just one power connection, and save time, materials needed and installation costs, with cost savings of up to 50%. The complete system can easily be lifted during installation with one meter at a time, because of the flexible cable connection which again will save time and hassle. With the sidewards light distribution pattern, the leaves can optimally transform the light into growing more yield. The shape of the GreenPower LED interlighting module is designed to minimize maintenance and prevent from diseases.

Key benefits

- Boost production by applying the right light at the right spot with a system efficacy of up to 3.0 µmol/J.
- Minimize your energy costs by choosing the most efficient interlighting module for your situation.
- Reduce installation costs thanks to daisy-chaining and plug and play design.
- Easy to install and maintain.

^{*} Based on a 400 V situation in Europe

Choose the best value for your situation



Specifications		2.5 m / 98"			2 m / 80"	
		RO		но	RO	но
Initial Photon Flux	µmol/s	220		300	175	240
Power consumption	w	79		100	64	81
System efficacy	µmol/J	2.8		3.0	2.7	3.0
Dimensions	cm	6.5 x 7.9		6.5 x 7.9		
	inch	2.55 x 3.11			2.55 x 3.11	
Weight (driver included)	kg	2.5			2.2	
Power factor		> 0.9				
Power input	V AC*	200-400				
Ingress protection rating		IP66				
Lifetime	hrs**	25.000				
Approval marks		CE, PSE, ANZI, UL/CSA***				
Warranty		3 years				

RO = regular output HO = high output

- * 50-60 Hz
- ** L90B50 (90% flux maintenance) (Ta 25 °C / 77 °F)
- *** UL/CSA pending approval


Placing lighting within the canopy of your high wire plants directs and focuses growth-stimulating light on the most vital part of the crop. You can then get the most out of your crop with a reduced energy usage during the complete lifetime of your interlighting.

To help you get the best solution for your situation, we offer two versions of the GreenPower LED interlighting system.

In case you're a grower and want to apply the highest amount of light possible and get the most yield possible, you'd best install the GreenPower LED interlighting module high output version with 300 µmol/s light output and a system efficacy of 3.0 µmol/J.

The interlighting module with 220 μ mol/s light output and 2.8 μ mol/J light efficiency gives you exactly what you need to increase your yields, when you're facing high energy costs, and can be especially beneficial for increasing yields of e.g. tomatoes and cucumbers, which are not affected by higher light levels.

The system comes in a 2 meter and 2.5 meter version, allowing you to tailor it to your specific situation and get a uniform light distribution right until the end of each row.



© Philips Lighting Holding B.V. 2016. All rights reserved. Philips reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.

Document order number: 32226 357 70668 V1

01/2017

Data subject to change



For more information about Philips Horticulture LED Solutions visit: www.philips.com/horti

Write us an e-mail: horti.info@philips.com

Or tweet us: @PhilipsHorti